

LEDForce 18 eXterior™

LEDForce 18 eXterior RGB and LEDForce 18 eXterior RGBW are perfect fit for any outdoor installations where both powerful output and IP 65 rating of is required.

**Light source**

18 x 3IN1 RGB LED or 18 x 4IN1 RGBW LED multichip

**Zoom range**

25° beam angle

**Effects**

Flicker free operation



Extremely bright 25°beam with no multicolor shadows is provided by new Tri-color and Quad-color LED technology 18 x 3IN1 RGB LED or 18 x 4IN1 RGBW LED multichip with optional 10° lens kit available. Die cast aluminum casting with double hanging brackets for mounting in any positions, LED set up and control display with auto shut function and Universal Internal Power supply are only few admirable features of many of this Par Can which is a good companion to any lighting designer.

Technical Specification

Technical specifications

- TriColor and Quadcolor LED Par Can for outdoor use
- 18 x 3 Watt Tri Color RGB LEDs and 18 x5 Watt Quad Color RGBW LEDs
- Tri-color and Quad-color LED technology for better colors and no multicolor shadows
- IP65 Die cast aluminum body
- Flicker free operation
- 4 operational modes: Sound Active, Macro, Auto, & DMX
- DMX 512 control protocol
- 4 DMX modes: 1,2,3 and 7 channels
- 5-pin XLR connector on 1 m IP DMX cable
- Double hanging brackets – for truss mounting and floor standing
- Standard beam angle: 25°
- Optional 10° lens kit available
- Long-life LEDs: 50.000 hours expected life time
- Very low heat output
- Universal Internal PSU : 90-260V, 50/60Hz
- Very low Power consumption : 65W / RGB and 95W / RGBW
- Dimensions : (LxWxH) 389 x 296 x 336mm / 14,4" x 13,1" x 11,7" (without hanging bracket)
- Weight : 7,1 Kg
- LED control display for set up and control
- Display auto shut off