

ROBIN® 300 Plasma Spot

The amazing ROBIN® 300 Plasma Spot Light is the first in a unique and new era of plasma lamp based fixtures from Robe.

Robin 300 Plasma Spot light is the first in a new generation of fixtures we have all been dreaming about! A perfect colour rendering index (CRI = 94), an extremely flat and even light beam (1:1.5) and a lifespan of 10.000 hours - all these fantastic features exist thanks to a brand new light source - the plasma lamp, which is now being introduced to the market. Moreover, the new plasma lamp source offers a dimming capability from 20-100% and a semi-hot restrike function (less than 120 sec. for full lamp brightness after shutting off).



Technical Specification

SOURCE

- Lamp: Plasma source
- Approved model: Lifi ENT 31-02, 266 W, Luminous Flux 18.000 Lm, CCT 5.400 K, CRI=94, lamp life 10.000 Hrs
- Control: Automatic and remote on/off

OPTICAL SYSTEM

- Beam angle: 10° - 40°

ELECTRICAL SPECIFICATION

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 390 VA at 230 V/50 Hz

MECHANICAL SPECIFICATION

- Height: 516 mm (20.3") - head in horizontal position
- Width: 433 mm (17.0")
- Depth: 470 mm (18.5")
- Weight: 21 kg (46.3 lbs)

THERMAL

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum surface temperature: 60 °C (140 °F)

STATIC GOBOS

- Metal gobos - outside diameter: 26.9 mm, image diameter: 22.5 mm, aluminium, thickness: 0.5 mm

ROTATING GOBOS

- Glass gobos - outside diameter: 26.8 mm, max. thickness: 4.0 mm, high temperature borofloat or better glass

CONTROL AND PROGRAMMING

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocol: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Control channels: 22, 24, 31
- 3 DMX protocol modes
- 3-editable programs, each up to 100 steps
- Stand-alone operation
- Optional wireless version available: CRMX™ technology from Lumen Radio

DISPLAY

- QVGA Robe touch screen with battery backup gravitation sensor for auto screen positioning operation memory service log with RTC

- Pan/Tilt resolution: 16bit
- Movement control: Tracking and vector
- Colour wheel positioning: 8 or 16bit
- Static gobo wheel positioning: 8 or 16bit
- Rotating gobos: 8 or 16bit
- Iris: 8 or 16bit
- Frost: 8bit
- Focus: 8 or 16bit
- Dimmer: 8 or 16bit
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Built-in analyzer for easy fault finding

ELECTROMECHANICAL EFFECTS


- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%
- CTO: 0-100%
- Colour wheel: 7 replaceable "SLOT&LOCK" dichroic filters + open, trapezoid shape
- Static Gobo wheel: 9 replaceable "SLOT&LOCK" metal gobos + open
- Rotating Gobo wheel: 7 rotating, indexable, replaceable "SLOT&LOCK" dichroic and black and white glass gobos + open
- Iris: Motorized, stepless, up to 3 Hz
- Prism: 3-facet 11° indexable prism rotating in both directions at different speeds
- Frost effect: separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect, Electronic strobing "ZAP"
- Motorized zoom and focus
- Pan: 540°
- Tilt: 280°

RIGGING

- Mounting points: 2 pairs of ¼-turn locks
- Fixation option: Pan/Tilt-lock mechanism
- 2 x Omega bracket with ¼-turn quick locks
- Safety chain/rope attachment point

gobos & colours

ROTATING GOBO WHEEL




15030028



15040023



15020190



15020191



15020192



15020195



15020193

STATIC GOBO WHEEL



15020143



15010733




15010732



15010731



15010730



15010719



15010729



15010728



15010727

COLOUR WHEEL



99011885



99011886



99011887



99011883



99011884



99011882



99011881