

ROBIN® 300E Spot

Onboard is a package of specially designed modular features including a large 10° - 40° zoom, CMY+CTO, static and rotating gobo wheels, colour wheel, frost, iris and many more.

ROBIN® 300E Spot light is a neat, punchy profile fixture with superior functions such as a large linear zoom and dynamic hot-spot control, ideal for a wide range of applications. A full package of rotating and static gobos plus full CMY+CTO and colour wheels give a standard base for any show. Advanced features like variable frost, linear iris, rotating prism and speedy mechanical shutters provide subtle and detailed in-tuning.



Technical Specification

SOURCE

- Lamp: Compact high-pressure metal halide lamp
- Base: PGJX28
- Approved model: Philips MSR Gold 300/2 MiniFastFit
- Control: Automatic and remote on/off
- Ballast: Electronic

OPTICAL SYSTEM

- Dichroic glass reflector for maximising the light efficiency
- Beam angle: 10° - 40°

ELECTROMECHANICAL EFFECTS

- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%
- CTO: 0-100%
- Hot-spot control: Hot-or-not-spot
- Colour wheel: 7 replaceable "SLOT&LOCK" dichroic filters + open, trapezoid shape
- Static Gobo wheel: 9 replaceable "SLOT&LOCK" metal gobos + open
- Rotating Gobo wheel: 7 rotating, indexable, replaceable "SLOT&LOCK" dichroic and glass gobos + open
- Iris: Motorized, stepless, up to 3 Hz
- Prism: 3-facet 11° indexable prism rotating in both directions at different speeds
- Frost effect: Separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect, Electronic strobbing "ZAP"
- Motorized zoom and focus
- Pan: 540°
- Tilt: 280°

CONTROL AND PROGRAMMING

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Control channels: 23, 25, 32
- 3 DMX protocol modes
- 3-editable programs, each up to 100 steps
- Stand-alone operation
- Display:
 - QVGA Robe touch screen with battery backup gravitation sensor for auto screen positioning operation memory service log with RTC
- Pan/Tilt resolution: 16bit
- Movement control: Tracking and vector
- Colour wheel positioning: 8 or 16bit
- Static gobo wheel positioning: 8 or 16bit
- Rotating gobos: 8 or 16bit
- Iris: 8 or 16bit
- Frost: 8bit
- Focus: 8 or 16bit

- Dimmer: 8 or 16bit
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Built-in analyser for easy fault finding
- Optional wireless version available: CRMX™ technology from Lumen Radio

STATIC GOBOS

- Metal gobos - outside diameter: 26.9 mm, image diameter: 22.5 mm, aluminium, thickness: 0.5 mm

ROTATING GOBOS

- Glass gobos - outside diameter: 26.8 mm, image diameter: 22.0 mm, thickness: 1.1 mm, max. thickness: 4.0 mm, high temperature borofloat or better glass

THERMAL

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 80 °C (176 °F)

RIGGING

- Mounting points: 2 pairs of ¼-turn locks
- Fixation option: Pan/Tilt-lock mechanism
- 2 x Omega bracket with ¼-turn quick locks
- Safety chain/rope attachment point

ELECTRICAL SPECIFICATION


- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 450 VA at 230 V/50 Hz

MECHANICAL SPECIFICATION

- Height: 516 mm (20.3") - head in horizontal position
- Width: 433 mm (17.0")
- Depth: 470 mm (18.5")
- Weight: 20 kg (44.1 lbs)

gobos & colours

ROTATING GOBO WHEEL




15030028



15040023



15020190



15020191



15020192



15020195



15020193

STATIC GOBO WHEEL



15020143




15010733



15010732



15010730



15010719



15010729



15010728



15010727

COLOUR WHEEL



99011881



99011882



99011884



99011883



99011887



99011886



99011885